



ExaGrid® EX10000E Appliance Series

Application Support

Backup Applications (File, Database, Email)

- CA ARCserve - 11.5, 12.0, 12.5
- Symantec Backup Exec - 11D, 11.5, 12.0, 12.5, 2010/OST
- Symantec NetBackup - 6.0, 6.5.x, 7.0/OST
- CommVault Simpana - 7.0, 8.0
- EMC NetWorker - 7.3, 7.4, 7.5, 7.6
- VMware files (VMDK) via supported backup applications and VMDK direct backups
- Vizioncore vRanger Pro - 3.x, 4.x
- Oracle Recovery Manager (RMAN) - 10 and 11

Backup Applications (continued)

- SQL Server 2000, 2005, 2008 Dumps
- Unix/Linux File System Dumps

Operating System File Backup

- Microsoft Windows
- Linux
- Novell NetWare
- UNIX

Backup Application Storage Protocol Support

- CIFS (Windows)
- NFS (UNIX / Linux)

Site Configuration

Primary Site Configuration / Capacity

- Scalable from 10TB per single appliance
- Up to 100TB per site
- Interoperates with all existing ExaGrid appliance models
- Supports up to 8 remote sites transferring data to a central site for a total of 9 sites
- Standard IP WAN connection between sites

Site Power Requirements

- Two NEMA 5-15R 3-prong receptacles per appliance
- Voltage: 100-240 VAC
- AMPS (typical): 4.6A @ 115, 2.2A @ 240
- Power: (typical) 530W
- Country kits available for international orders

Operating Environment

- 10° to 35°C (50° to 95°F)
- Cooling: 1850 BTU/Hr.
- 20% to 80% (non-condensing)

Regulatory Approvals (US, Canada, EU)

Safety

- UL/CSA 60950-1 2d Ed.
- IEC 60950 -1:2005
- EN 6095-1:2006
- CD Certificate and Report

Emissions

- FCC Class A
- EN55022:2006 + A1:2007
- 47 CFR Part 15 (FCC) Class A limits
- ICES-003 Issue 4
- AS/NZS CISPR 22:2006
- Japan VCCI

Immunity

- EN55024:1998 + A1:2001 + A2:2003

Agency

- RoHs compliant
- WEEE Declaration for E.U. Directive

System Hardware Components

ExaGrid EX10000E Appliance

- Intel Xeon Quad-core processors
- Enterprise SATA drives
- RAID6 with hot spare
- ExaGrid software
- 4U, 19-inch, rack-mount chassis
- Redundant fans
- Mirrored hot-plug power supplies
- Qty 4 or 6 10/100/1000 Ethernet ports
- Qty 2 10 GbE ports (optional, CX4 or SFP+) (replaces 2 10/100/1000 ports)